

MULTI - FORMAT LCD RACK MONITOR

# PRM-702



12G-Dual 7" LCD

3RU Multi-Channel Rack Monitor



- 12G-SDI
- Blue Only
- HDR
- H/V Delay
- Scan (Zero, Over)
- Audio Level Meter
- Markers (Custom Marker)
- Time Code
- UMD (TSL 3.1)
- Aspect

- Waveform
- Vector Scope
- Internal Pattern
- Tally (3 Colors)
- User Preset Save/Load
- 3D LUT
- Gamma
- RS-422 IN/OUT
- Remote (GPI Control)
- USB(Update, Calibration)

## Specifications

Spec		PRM-702
Screen number / Rack Size(19")		Dual / 3RU
Display	Size	7"
	Resolution	1920 x 1200
	Active Area (W x H)	151.2mm (W) X94.5(H)mm
	Pixel Pitch	0.078mm x 0.078mm
	Color	16.7M
	Viewing Angle	160(H), 160(V)
	Luminance of White	1000cd/m <sup>2</sup>
Contrast		1200:1
Input	SDI	2 x 12G SDI
	HDMI®	1x HDMI® 2.0
Input Signal Format	SMPTE ST 2082-10(12G Single)	2160p(60/59.94/50/30/29.97/25/24/23.98)
	SMPTE ST 2081-10(6G Single)	2160p(30/29.97/25/24/23.98)
	SMPTE ST 425-AB	1080p(60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
		1080i (60/59.94/50)
	SMPTE ST 274	1080p(30/29.97/25/24/23.98/24sF/23.98sF)
		1080i (60/59.94/50)
	SMPTE ST 296	720p(60/59.94/50)
	SMPTE ST 260	1920 x 1035i(60/59.94)
	SMPTE ST 2048	2048 x 1080p(24/23.98/24sF/23.98sF)
	SMPTE ST 125	480i(59.94)
ITU-R BT.656	576i(50)	
HDMI®	HDMI® 2.0 2160p(60)	
Output	SDI	1 x 12G SDI(A,B Selecte)
Audio	Audio Out	1 x Phone Jack
	Speaker	2 x STEREO
Control	RS-422	o
	Remote (GPI Control)	o
	USB(Update, Calibration)	For Firmware Update, Color Calibration
General	Power Requirements	DC12V / 5A
	Power Consumption	W
	Operating Temperature	0 ~ 40°C(32°F ~ 104°F)
	Operating Humidity	20% ~ 80% RH
	Dimensions (with RMK)	480 x 132.3 x 45 mm / 19.89 x 5.20 x 1.77 inch
	Weight	kg / lbs
Accessories		DC Power Adapter / Power Cable

\* Specifications are subject to change without prior notice for the product quality improvement.

**postium**® **POSTIUM KOREA Co., Ltd.**  
[www.postium.com](http://www.postium.com)  
[sales@postium.com](mailto:sales@postium.com)