

MULTI - FORMAT LCD RACK MONITOR

PRM-702



Dual 7" LCD

3RU Multi-Channel Rack Monitor



User Aspect

Various Scan Mode

Waveform

Vector Scope

Internal Pattern Display

Tally (3 Colors)

User Preset Save/Load

Gamma

Blue Only

H/V Delay

Scan (Zero, Over, Pixel-to-Pixel)

Zoom

Audio Level Meter

Key Lock

Markers (Custom Marker)

Time Code Display

UMD (TSL 3.1)

Specifications

Spec		PRM-702
Screen number / Rack Size(19")		Dual / 3RU
Display	Size	7"
	Resolution	1920 x 1200
	Active Area (W x H)	151.2mm (W) X94.5(H)mm
	Pixel Pitch	0.078mm
	Color	16.7M
	Viewing Angle	160(H), 160(V)
	Luminance of White	1500cd/m ²
Input	Contrast	1200:1
	SDI	2 x 3G SDI
	HDMI	1
Input Signal Format	Analog	1xBNC(Composite)
	SMPTE ST 425-AB	1080p(60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
		1080i (60/59.94/50)
	SMPTE ST 274	1080p(30/29.97/25/24/23.98/24sF/23.98sF)
		1080i (60/59.94/50)
	SMPTE ST 296	720p(60/59.94/50)
	SMPTE ST 260	1920 x 1035i(60/59.94)
	SMPTE ST 2048	2048 x 1080p(24/23.98/24sF/23.98sF)
SMPTE ST 125	480i(59.94)	
Output	ITU-R BT.656	576i(50)
	HDMI	1.4b(1080p(50/60))
	SDI / HDMI	2 x 3G SDI
Audio	Audio In	1 x Phone Jack
	Audio Out	1 x Phone Jack
	Speaker	2 x STEREO
Control	Ethernet	x
	RS-422	o
	Remote (GPI Control)	o
	USB(Update, Calibration)	For Firmware Update, Color Calibration
General	Power Requirements	DC12V / 5A
	Power Consumption	32W
	Operating Temperature	0 ~ 40°C(32°F~104°F)
	Operating Humidity	20% ~ 80% RH
	Dimensions (with RMK)	480 x 132.3 x 45 mm / 19.89 x 5.20 x 1.77 inch
	Weight	2.24kg / 4.93lbs
Accessories	DC Power Adapter / Power Cable	

* Specifications are subject to change without prior notice for the product quality improvement.

 **POSTIUM KOREA Co., Ltd.**
www.postium.com
sales@postium.com