

MULTI - FORMAT LCD RACK MONITOR

PRM-434

NEW

Quad 4.3" LCD

2RU Multi-Channel Rack Monitor



Various Scan Mode

Waveform

Vector Scope

Internal Pattern Display

Tally (3 Colors)

Gamma

Blue Only

H/V Delay

can (Zero, Over, Pixel-to-Pixel)

Zoom

Audio Level Meter

Key Lock

Markers (Custom Marker)

Time Code Display

UMD (TSL 3.1)

Specifications

| Spec | | PRM-434 |
|--------------------------------|--------------------------------|---|
| Screen number / Rack Size(19") | | Quad / 2RU |
| Display | Size | 4.3" |
| | Resolution | 800 x 480 (15:9) |
| | Active Area (W x H) | 95.04mm (W) X53.858(H)mm |
| | Pixel Pitch | 0.11mm |
| | Color | 16.7M |
| | Viewing Angle | 160(H), 160(V) |
| | Luminance of White | 800cd/m ² |
| Input | Contrast | 1200:1 |
| | SDI | 1 x 3G SDI |
| | HDMI | - |
| Input Signal Format | Analog | 1xBNC(Composite) |
| | SMPTE ST 425-AB | 1080p(60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF) 1080i (60/59.94/50) |
| | SMPTE ST 274 | 1080p(30/29.97/25/24/23.98/24sF/23.98sF) 1080i (60/59.94/50) |
| | SMPTE ST 296 | 720p(60/59.94/50) |
| | SMPTE ST 260 | 1920 x 1035i(60/59.94) |
| | SMPTE ST 2048 | 2048 x 1080p(24/23.98/24sF/23.98sF) |
| | SMPTE ST 125 | 480i(59.94) |
| | ITU-R BT.656 | 576i(50) |
| Output | SDI | 1 x 3G SDI |
| Control | RS-422 | 1 x Input, 1 x Output |
| | Remote (GPI Control) | 4(1 for each screen) |
| | USB(Update, Calibration) | For Firmware Update, Color Calibration |
| General | Power Requirements | DC12V / 3.5A |
| | Power Consumption | 32W |
| | Operating Temperature | 0 ~ 40°C(32°F~104°F) |
| | Operating Humidity | 20% ~ 80% RH |
| | Dimensions (with RMK) | 480 x 86.5 x 50 mm / 19.89 x 3.40 x 1.96 inch |
| | Weight | 1.94kg / 4.27lbs |
| Accessories | DC Power Adapter / Power Cable | |

* Specifications are subject to change without prior notice for the product quality improvement.



POSTIUM KOREA Co., Ltd.
www.postium.com
sales@postium.com