

MULTI - FORMAT LCD RACK MONITOR

PRM-434

NEW

Quad 4.3" LCD 2RU Multi-Channel Rack Monitor



- Various Scan Mode
- Waveform
- Vector Scope
- Internal Pattern Display
- Tally (3 Colors)
- Gamma
- Blue Only
- H/V Delay
- can (Zero, Over, Pixel-to-Pixel)
- Zoom
- Audio Level Meter
- Key Lock
- Markers (Custom Marker)
- Time Code Display
- UMD (TSL 3.1)

Specifications

Spec		PRM-434
Screen number / Rack Size(19")		Quad / 2RU
Display	Size	4.3"
	Resolution	800 x 480 (15:9)
	Active Area (W x H)	95.04mm (W) X53.858(H)mm
	Pixel Pitch	0.11mm x 0.11mm
	Color	16.7M
	Viewing Angle	160(H), 160(V)
	Luminance of White	800cd/m ²
Input	Contrast	1200:1
	SDI	1 x 3G SDI
	HDMI	-
Input Signal Format	Analog	1xBNC(Composite)
	SMPTE ST 425-AB	1080p(60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
		1080i (60/59.94/50)
	SMPTE ST 274	1080p(30/29.97/25/24/23.98/24sF/23.98sF)
		1080i (60/59.94/50)
	SMPTE ST 296	720p(60/59.94/50)
	SMPTE ST 260	1920 x 1035i(60/59.94)
	SMPTE ST 2048	2048 x 1080p(24/23.98/24sF/23.98sF)
Output	SMPTE ST 125	480i(59.94)
	ITU-R BT.656	576i(50)
Control	SDI	1 x 3G SDI
	RS-422	1 x Input, 1 x Output
	Remote (GPI Control)	4(1 for each screen)
General	USB(Update, Calibration)	For Firmware Update, Color Calibration
	Power Requirements	DC12V / 3.5A
	Power Consumption	32W
	Operating Temperature	0 ~ 40°C(32°F~104°F)
	Operating Humidity	20% ~ 80% RH
	Dimensions (with RMK)	480 x 86.5 x 50 mm / 19.89 x 3.40 x 1.96 inch
	Weight	1.94kg / 4.27lbs
Accessories	DC Power Adapter / Power Cable	

* Specifications are subject to change without prior notice for the product quality improvement.



POSTIUM KOREA Co., Ltd.
www.postium.com
sales@postium.com